

badgy

Evolis presents **Badgy**, the printer designed to let you easily make your own professional-quality color badges.

Badgy is a complete, simple and cost-effective solution for delivering personalized cards, in small to medium runs or individually.



THE AFFORDABLE CARD PRINTER

Badgy is ideal for instant issuance of visual identification cards:

- Employee badges
- Student IDs
- Member cards
- Loyalty cards
- Event passes
- Business cards

COMPLETE SOLUTION

With the Badgy printer, you have a **turn-key solution** including a professional plastic card printer, card personalization software, a color print ribbon and 100 blank plastic cards. In addition, a **free card template library** is available on www.badgy.com. Personalize the template of your choice with your own texts, logos, pictures, barcodes or create your own template.

EASE OF USE

You set up and use Badgy just like a **standard office printer**. Place the blank cards in the feeder tray, click print and your printed cards are delivered to the tray in front, **ready to use**. The online template library also makes it easy to design your own cards.

TIME SAVING

Get a color card in less than a minute! Badgy lets you print your cards instantly, individually or in volume. No more waiting, for you or your customers!

COST-EFFECTIVE SOLUTION

With a **cost-effective per-card print price**, issuing cards is affordable, even in small quantities. You can print **as needed, when needed**, in quantities that are right for you. Compared to outsourcing, your investment will pay for itself if you print just 200 color cards per year.

ENHANCED BRAND IMAGE

The Badgy printer produces **professional-quality** personalized plastic cards with your logo, which enhances the image of your organization. Impress your customers with **top quality cards**.

COMPACT DESIGN

Particular attention was paid to the design of the Badgy printer: with its clean look and its small footprint - smaller than a sheet of paper - it **fits seamlessly** into your workspace.



evolis
card printers

badgy



- LED control panel
- Print module 40 sec per color card



- 100-card feeder
- USB port
- Easy to install ribbon cartridge
- Retractable 10-card output tray

GENERAL FEATURES

- Single-sided printing module
- Maximum printable area: 51.38 x 82.8 mm (2.02" x 3.26") margin of 1.35 mm (0.05")
- Color dye sublimation, monochrome thermal transfer
- 300 dpi print head
- 2 million colors
- 16 MB of memory (RAM)

PRINTING PERFORMANCES¹

- Color (YMCKO): 40 s per card
- Monochrome: 17 s per card

INTERFACES

- USB 1.1 (USB 2.0 compatible)

DISPLAY

- Printer LEDs
- Graphic alerts²: cleaning alerts, ribbon finished / almost finished alert, etc.

RESIDENT FONTS

- Arial, Arial bold
- Barcode: Code 39, Code 128, EAN, Interleaved 2/5

CARD MANAGEMENT AND SPECIFICATIONS

- Detachable feeder capacity: 100 cards
- Output tray capacity: 10 cards
- Card thickness: 0.50 mm (20 mil) to 0.76 mm (30 mil), automatically adjusts to thickness
- Card types:
 - PVC cards
 - Laminated PVC cards
 - Composite PVC cards
 - PET cards
- Card format: ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 2.125" x 3.375")

EVOLIS HIGH TRUST[®] RIBBONS

To maximise the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust[®] ribbons.

- Ribbon capacity:
 - YMCKO: 100 prints/roll
 - Monochrome ribbon (optional): 600 prints/roll³
- Cartridge format for easier handling

SOFTWARE

- Delivered with Office Card for personalizing and printing badges (compatible with Windows[™]: XP SP3, Vista 32/64, W7 32/64, W8 32/64)
- Delivered with a driver for Windows[™] XP SP3, Vista 32/64, W7 32/64, W8 32/64
- Delivered with a driver for Mac OS X (from 10.5 onwards)
- Minimum system requirements: 500 MHz processor, 512 MB RAM, Internet connection

CERTIFICATIONS AND STATEMENT OF COMPLIANCE

- Automatic sleep mode
- CE, FCC, VCCI, CCC

POWER

- Power supply: 100-240 V AC, 50-60 Hz, 1.5 or 1.8 A
- Printer: 24 Volts DC, 3 A

OPERATING ENVIRONMENT

- Min / max operating temperature: 15° / 30° C (59° / 86° F)
- Humidity: 20% to 65% non-condensing
- Min / max storage temperature: -5° / +70° C (23° / 158° F)
- Storage humidity: 20% to 70% non-condensing
- Operating ventilation: open air

PACKAGING CONTENT

- Printer
- Consumables:
 - Color ribbon (YMCKO) for 100 cards
 - 100 blank PVC cards 0.50 mm / 20 mil
 - Cleaning kit
- Installation CD (printer driver, software and card templates)
- Power supply and cord
- USB cable

SIZE AND WEIGHT

- Dimensions (H x W x D):
 - Without the output tray: 166 x 194 x 271 mm (6.54" x 7.64" x 10.67")
 - With the output tray: 166 x 194 x 374 mm (6.54" x 7.64" x 14.72")
- Weight: 2.4 kg (5.29 lbs)

WARRANTY⁴

- 1 year (printer and print head), unlimited number of passes
- Warranty extension available as an option

¹ Speed measured from the time the sensor detects the card to the time the card is ejected

² Depends on your version of Windows[™]

³ Under specific conditions

⁴ Warranty subject to observance of specific conditions and use of Evolis High Trust[®] ribbons

UAE

Sifat It Solutions LLC

Tel. +97 4 3542953

Mail. info@sifatit.com

Web. www.sifatit.com

EUROPE - MIDDLE-EAST - AFRICA

Evolis Card Printer - 14 avenue de la Fontaine - ZI Angers-Beaucouzé
49070 Beaucouzé - France

T +33 (0) 241 367 606 - F +33 (0) 241 367 612 - info@evolis.com

AMERICAS - Evolis Inc. - Fort Lauderdale - evolisinco@evolis.com

ASIA-PACIFIC - Evolis Asia Pte Ltd - Singapore - evolisasia@evolis.com

INDIA - Evolis India - Mumbai - evolisinia@evolis.com

CHINA - Shanghai - infochina@evolis.com

www.evolis.com

KYOCERA

Printhead

evolis
card printers