

# ZD220 4-Inch Value Desktop Printer



Reliable operation, quality construction, unsurpassed value

Not all printers are created equally, especially basic models. To reduce costs, value printers are often constructed using less expensive components. Many fail to perform under more demanding duty cycles, create delays and downtime for repairs, and require replacement after only a few years of use. Instead of conserving budget, customers are left with greater expense and hassle.

Zebra does it differently. The ZD220 desktop printer gives you reliable operation and basic features at an affordable price—both at the point of purchase and across the entire lifecycle. Engineered with Zebra quality, it boasts a dual-wall construction for added durability. And, it is ENERGY STAR® qualified to reduce your operational expenses. Built to last for years, the ZD220 provides an outstanding return on your investment.



## Get Printing Quickly

The ZD220 is simple to install and begin printing—right out of the box. USB connectivity allows for universal interoperability. Easily replace legacy printers using ZPL, EPL or non-Zebra command languages. And, media changes are expedited with Zebra's OpenACCESS™ clamshell design. It is ideal for use in transportation and logistics, light manufacturing, retail and healthcare applications to print a variety of tickets, tags, passes, labels and receipts.

## Basic Features for Simple Operation

This 4-inch printer produces labels quickly, up to 4" per second, to keep your workflows moving. Increased memory allows you to store more fonts and graphics. A single LED indicator and single button for feed/pause make it easy to operate and identify printer status. Choose from direct thermal or thermal transfer models, and add an optional factory-installed peeler. The ZD220 features a core set of Print DNA software applications, powered by Link-OS® Basic, to deliver a cost-effective and dependable print experience.

## Backed by Zebra's Worldwide Service and Support

Access repair support services, live-agent technical support and software support quickly anywhere around the globe through Zebra and its trusted network of more than 10,000 partners. Zebra OneCare™ provides enhanced coverage that exceeds standard warranty for normal wear and tear, priority repair turnaround times at the depot and more—all for a tiny fraction of the cost of a single repair.

## Consistently Exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer—and peace of mind for you. For industry-leading quality, service and thermal printing expertise, choose Zebra Certified Supplies.



Reliable, quality printing that matches your budget.  
For more information, visit [www.zebra.com/zd220](http://www.zebra.com/zd220)



# ZD220 Specifications

## Standard Features

Thermal Transfer or Direct Thermal print method  
 ZPL and EPL programming languages  
 Single LED status indicator  
 Single button for feed/pause  
 USB connectivity  
 OpenACCESS™ for easy media loading  
 Dual-wall frame construction  
 ENERGY STAR qualified

## Physical Characteristics

<b>Dimension</b>	Thermal Transfer: 10.5 in. L x 7.75 in. W x 7.5 in. H 267 mm L x 197 mm W x 191 mm H Direct Thermal: 8.6 in. L x 6.9 in. W x 5.9 in. H 220 mm L x 176 mm W x 151 mm H
<b>Weight</b>	2.5 lbs./1.1 kg

## Printer Specifications

<b>Resolution*</b>	203 dpi/8 dots per mm
<b>Memory</b>	256 MB Flash; 128 MB SDRAM
<b>Maximum Print Width</b>	4.09 in./104 mm
<b>Maximum Print Speed</b>	4 in./102 mm per second
<b>Media Sensors</b>	<ul style="list-style-type: none"> <li>• Movable black marks sensor, limited range from center to left side</li> <li>• Fixed off-center gap sensor</li> </ul>
<b>Firmware</b>	ZPL II; EPL 2; XML

## Media and Ribbon Characteristics

<b>Maximum Label Length</b>	39.0 in./991 mm
<b>Media Width</b>	1.00 in. / 25.4 mm to 4.4 in. / 112 mm
<b>Media Roll Size</b>	5.00 in./127 mm outer diameter Core inner diameter: 0.5 in. (12.7 mm) and 1.0 in. (25.4 mm) standard, 1.5 in. (38.1), 2.0 in., (50.8 mm) and 3.0 in. (76.2 mm) using optional adapters
<b>Thickness</b>	0.003 in. (0.08 mm) min.; 0.0075 in. (.1905 mm) max. (tear-off mode only)
<b>Media Types</b>	Roll-fed or fan-fold, die cut or continuous with or without black mark, tag stock, continuous receipt paper, and wristbands
<b>Ribbon Outside Diameter</b>	1.34 in./ 34 mm (74 m)
<b>Maximum Ribbon Length</b>	244 ft. (74 m)
<b>Ribbon Ratio</b>	1:1 media to ribbon (74 m)
<b>Ribbon Width</b>	1.33 in./ 33.8 mm ~ 4.3 in./ 109.2 mm
<b>Ribbon Core I.D.</b>	74 Meter ribbon 0.5 in./ 12.7 mm

PRODUCT SPEC SHEET

ZD220 VALUE DESKTOP PRINTER

# ZD220 Specifications

Operating Characteristics	
Operating Temp.	40° to 105° F/4.4° to 41° C
Storage Temp.	-40° to 140° F/-40° to 60° C
Operating Humidity	10% to 90% non-condensing
Storage Humidity	5% to 95% non-condensing
Electrical	Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz; ENERGY STAR qualified
Operations and Accessories	
Media Handling	Factory installed peeler
Real Time Clock	None
Fonts/Graphics/Symbologies	
Bar Code Ratios	2:1 and 3:1
1D Bar Codes	Code 11, Code 39, Code 93, Code 128, ISBT-128, UPC-A, UPC-E, EAN-8, EAN-13, UPC and EAN 2-or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar and Planet Code
2D Bar Codes	Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Code, MicroPDF, Aztec
Fonts and Graphics	16 resident expandable ZPL II bitmap fonts Two resident scalable ZPL fonts Five resident expandable EPL2 fonts Native open-type font support Unicode compliant for multi-language, on demand thermal printing China units include SimSun simplified Chinese font 50 MB user available non-volatile memory, 8 MB user available SDRAM

## Printers Supplies

Keep your Zebra printer up and running with genuine Zebra printer supplies, available directly from Zebra.

## Regulatory

- IEC 60950-1, EN55022 Class B, EN55024, EN61000-3-2, EN61000-3-3, FCC Class B, ICES-003, FCC 15.209; 15.247(d), ICRSS 247, EN 300328, EN 301 893, EN 62311, cTUVus
- CE Marking, VCCI, C-Tick, S-Mark, CCC, CU, BSMI, KCC, SABS, IN-Metro, BIS, NOM

## Recommended Services

Zebra OneCare SV

## Print DNA Software

This printer is supported by a core set of PrintDNA applications powered by Link-OS® Basic.

Print DNA features may vary by model and a Support Contract may be required. For more information, please visit [www.zebra.com/printdna](http://www.zebra.com/printdna)

## Product Warranty

ZD200 series printers are warranted against defects in workmanship and materials for a period of 2 (two) years from the date of shipment. For the complete warranty statement, please visit: [www.zebra.com/warranty](http://www.zebra.com/warranty).



ZEBRA and the stylized Zebra head are trademarks of Zebra Technologies Corporation, registered in many jurisdictions worldwide. All other trademarks are the property of their respective owners. ©2020 Zebra Technologies Corporation and/or its affiliates. All rights reserved.  
Part number: SS-ZD220 06/01/2020